

## TECHNICAL DATA



### Description

**Paver Tiles** are a 1/2" or 3/4" thick resilient and skid resistant rubber tile surfacing alternative to traditional commercial flooring materials.



Go GREEN



Be SAFE

**Paver Tiles** are manufactured from 100% post-consumer California waste tires and provide an exceptionally durable, safe, low maintenance option to bare concrete or other hard surface materials.

### Uses

**Paver Tiles** are ideally suited to improve the beauty, comfort and ease of maintenance in various environments including fitness centers, shopping malls, daycare centers, churches, walkways, garages and even around swimming pools.

### Advantages

- Paver Tiles are exceptionally durable and resilient and provide years of performance.
- **Paver Tiles** are water permeable providing a fast drying surface that easily permits surface water to properly drain.
- **Paver Tiles** are environmentally friendly, molded from 100% California recycled waste tires diverting as many as 2.5 tires per tile from our landfills.
- **Paver Tiles** are safe containing no toxic materials and certified to be 99.9% steel free.
- **Paver Tiles** have a very smooth top surface providing comfort to bare feet, hands and elbows while maintaining exceptional skid resistance whether wet or dry.
- **Paver Tiles** absorb shock making them more comfortable to walk on than traditional hardscape materials.

### Advantages (Continued)

- **Paver Tiles** are modular in design making them easy to install over the largest selection of sub-grades including concrete, asphalt, wood decking and compacted gravel.
- **Paver Tiles** are easy to maintain requiring only basic cleaning with a broom, vacuum or water hose on a regular basis.
- **Paver Tiles** come in a variety of colors providing a multitude of design options to meet any need.
- **Paver Tiles** are backed by the industries leading manufacturer of rubber molded safety tiles and accessories and come with a 5 Year Limited Material Warranty.

### Standard Colors



Black

Blue




Red

Gray




Earth

Green




Green Black

Gray Black



Blue Black

Tan Black



Red Black

### Product Specification

Tile Size:	24" x 24" ± 1/8"
Tile Thickness:	1/2", 3/4"
Tile Weight:	9lb, 12.75lb

### Physical Properties

Characteristic	Test	Result
Flame Spread:	ASTM E108	Class A
Flammability:	ASTM E648	Class II
Flammability:	ASTM 2859	Pass
Toxicity:	ASTM 2075	Lead Free
Slip Resistance:	ASTM F1677	Dry 0.63, Wet .052
Skid Resistance:	ASTM E303	Dry 96, Wet 47
Tensile Strength:	ASTM D412	1175.3 psi
Wear Resistance:	ASTM D3884	1.64% Loss/3000c
UV Resistances:	QPanel QUV	<3.0/4032 ksqm

### Finish Options

**Paver Tiles** are available in Flat Top or Brick Top patterns in 11 standard colors. (Brick Top only available in 3/4")