



PRODUCT DESCRIPTION

1 (888) 836-2665



Protect Your Animals.... Protect your Investment

- Manufactured from 100% post consumer waste tires
- 1" Thick with a paver bottom providing superior cushioning and durability without allowing permanent indentions to form
- Available in Flat Top or with a Brick Top Pattern

BENEFITS:

- Easy to Install modular design allows fully adhered or floating applications
- Safe non-toxic and steel free
- Easy to Maintain requires only basic cleaning with a broom, vacuum or hose
- Long Lasting water permeable and fast drying. Won't rot, decompose or attract insects.











TECHNICAL DATA

Description

Equi-Tile paver's are manufactured for the comfort and safety of your livestock and provide an environmentally friendly alternative to traditional equestrian flooring materials that is comfortable underfoot while providing slip resistance either wet or dry.

Uses

Equi-Tile paver's tiles are ideally suited to improve the beauty, comfort and ease of maintenance in your barn, wash racks, breezeways or trailers.

Advantages

- **Equi-Tile** paver's are designed to meet the demanding requirements of high traffic areas.
- **Equi-Tile** paver's are water permeable providing a fast drying surface that easily permits surface water to properly drain.
- **Equi-Tile** paver's are environmentally friendly, molded from 100% California recycled waste tires diverting as many as 1.4 tires per tile from our landfills.
- **Equi-Tile** paver's are safe containing no toxic materials and certified to be 100% steel free.
- **Equi-Tile** paver's have a very smooth top surface providing comfort under foot while maintaining exceptional skid resistance whether wet or dry.
- Equi-Tile paver's have a 1" thickness combined with the paver bottom density provides excellent cushioning for your livestock without allowing permanent indentations to form in the tiles.

Advantages (Continued)

- **Equi-Tile** paver's are modular in design making them easy to install over concrete and asphalt.
- Equi-Tile paver's can be installed using EMC's unique Konnector Pin System that creates a finished installation that will not readily shift or slide but still allows the flooring system to be moved when needed.
- **Equi-Tile** paver's are easy to maintain requiring only basic cleaning with a broom, vacuum or water hose on a regular basis.
- **Equi-Tile** paver's are backed by the industries leading manufacturer of rubber molded safety tiles and accessories and come with a 5 Year Limited Material Warranty.

Product Specification

Tile Size: 23 7/8" x 23 7/8" $\pm 1/8$ "

Tile Thickness: 1"

Tile Weight: 16,75lb

NOTE: Recycled Rubber Tiles will expand and contract with changes in UV Exposure and Temperature. Size tolerance is measured at 72° Fahrenheit.



- Equi-Tile Paving and Matting tiles are available in a variety of pigmented crumb rubber color selections providing a wide selection of color options to meet the most demanding design needs.
- **Equi-Tile** accessory pieces are available to complete your installation. Options include:
 - Ramps

Accessory pieces are available in limited color options. Refer to the SportPlay Mat Color Selection Chart for options.

• **Equi-Tile** can be installed over concrete and asphalt.

•

